

Specifications

General Specifications (without operator and without attachments)
(Approximate Only)

Overall width	840mm-1040mm
Overall length (without attachment)	1565mm
Overall height	1200mm
Max. operating height (with standard bucket)	2080mm
Operating weight	700-800kg
Turning radius with standard bucket	1300mm
Safe Working load (=50% of tip load)	250 kg
- bucket (& 90kg operator)	
(Lifting capacity up to 500kg with certain attachments)	
Speed	0 - 6 km/hr
Angle of departure	20 degrees
Engine HP	Kohler 22 HP
	Perkins 20 HP
Wheel motor sizes	29 cu in
Wheel base	710-800mm
Drive chain	ASA 60H (Heavy Link 3/4")
Ground clearance	135mm
Tyre size	18 x 8.50 x 8 (4 ply) standard
Hydraulics	2 pump
Pump sizes	Kohler 9 & 3 cc (3600 rpm)
	Perkins 11.2 & 3.15 cc (3100 rpm)
System relief pressure (hydraulic)	3000psi (206 Bar)
Hydraulic reservoir capacity	60 litres
Hydraulic output	43 litres per minute
Filtration	25 micron
Standard bucket capacity	0.11 cu m
Standard bucket dump height	1240 mm
Reach fully raised standard bucket	600mm
4 in 1 bucket capacity	0.11 cu m
4 in 1 bucket dump height	1750mm
Reach fully raised 4 in 1 bucket	600mm
Chip bark bucket capacity	0.18 cu m
Height to hinge pin (std. bucket in highest position)	1680mm

Specifications and design subject to change without notice.

